🔇 КУОСЕRа

Experience highperformance printing

Specifically designed for medium and large-sized work groups, the ECOSYS PA4500cx is an A4 colour device that brings running costs to a minimum while ensuring the utmost levels of productivity. This versatile printing device prints on a wide variety of media sizes and weights, up to 220g/m2.

							+ +
				+			+ +
				+			
					1		+
							. +
					r		. +
	ECOSY	S PA4	 500сх			Ready to print. PL A4 YesA4 Status II Forer 3 III to C 0 2000	• +
	A4 colo	our an	d b/w	printer			+
Up to 45 pages per minute							+
	Double	-sidec	l print a				
Compact design with full functionality							
					Evel		

GENERAL

KYOCERA ECOSYS Laser Colour Printer Operation panel: 21 characters / 5Line display with back light and numeric keypad

Type: Desktop Engine speed: Up to 45 pages A4 per minute Duplex print speed: 37 pages per minute, A4 Resolution: 1200 x 1200 dpi (print) Recommended Print Volume¹: 2,400 images per month Maximum Print Volume1: 100,000 images per month Maximum Life¹: 600,000 images or 5 years Warm-up time: Approx. 20 seconds or less Time to first print: Approx. 5.1 seconds or less CPU: ARM Cortex-A9 Dual core 1.2GHz

Memory: Standard 1 GB Max. 3GB + 64GB SSD / 256GB SSD / 512GB SSD **Standard interfaces:** USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BASE-T/100BASE-TX/ 1000BASE-T), optional Wireless LAN (IEEE 802.11b/g/n), 1 x eKUIO slot for optional devices, Slot for optional SD Card Integrated accounting: 100 department codes Dimensions (W x D x H): Without packaging: $394 \times 533 \times 455$ mm (without protrusions) $480 \times 576.5 \times 571.5$ mm (including protrusions) With packaging: 702 x 567 × 617 mm Weight: Without packaging: Approx. 33 kg (with bundled toner) Approx. 34 kg (without bundled toner) With packaging: 41 kg **Power source:** AC 220 ~ 240 V, 50/60 Hz Power consumption: Printing: 576.8 W Ready mode: 11.8 W Sleep-mode: 0.4 W (default) Noise (sound pressure level: ISO 7779/ISO 9296): Operating: 54 dB (LpAm) Stand-by: 30 dB (LpAm) Safety standards: TÜV/GS, CE This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

down with paper full sensor

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions **Input capacity:** Multi-purpose tray: 100 sheets (80 g/m² equivalent), 110 sheets (64 g/m² equivalent); 60-220 g/ m²; A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (70 x 140 to 216 x 356 mm), Banner paper up to 1220 mm. Standard universal paper cassette: 550 sheet with 75 g/ m2, 600 sheet with 64 g/m²; 60–220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 x 140 to 216 x 356 mm) Max. input capacity with options: 2,850 sheets with 75 g/m2, 3,110 sheets with 64 g/m² **Duplex:** Standard duplex unit; 60—163 g/m2; A4, A5, A6, B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm) Output capacity: 500 sheets (Equivalent to 80 g/m2) face

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible), PDF, XPS, Open XPS, TIFF, JPEG, URF, PWG Raster, PCLm **Operating systems:** All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, Linux, as well as other operating systems on reques Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 types of onedimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Print features: PDF Direct Print, Internet printing IPP 1.0, E-mail printing, WSD print, secure printing IPP over TLS, Local and network authentication, Network data encryption IPsec, HTTPS, LDAP over TLS, SNMPv3, SMTP over TLS, POP over TLS, Encrypted PDF Direct Print, TLS 1.3, Microsoft Universal Print, Printing for Chrome OS Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Microsoft Universal Print, Wi-Fi Direct (Opt)

SECURITY FEATURES

Secure Boot3, Run-time Integrity Check3, Allowlisting, TLS 1.3, IPSec, HTTPS, SNMPv3, "Confidential printing" with PIN code request, encrypted PDF direct printing, Security watermark, IPP over TLS, Enhanced WSD (TLS), network authentication (Kerberos, NTLM, 802.1x), restriction of the user group through user login management, IP filters, port number restrictions. Blocking interfaces, security Quick setup, adjustable administrator authentication for firmware updates, SIEM support (SysLog), SCEP, OCSP & CRL4, free activation of "Data Security Kit" functionality (e.g. data encryption, overwriting data no longer required) when installing an optional hard drive, data cleaning (resetting in the device stored information to factory settings, e.g. B. System settings or stored in a user box data), optional: TPM (Trusted Platform Module)

CONSUMABLES

Average continuous toner yield in accordance with ISO 19798 TK-5390K: Black toner 18,000 pages A4 TK-5390Y, TK-5390M, TK-5390C: Yellow, Magenta and Cyan 13,000 pages for A4. Starter toner black 8,000 pages and Yellow, Magenta and Cyan 6,000 pages A4

OPTIONS

PF-5150 Paper feeder: Max. 550 sheet with 75 g/m2, 600 sheet with 64 g/m2, 60 - 220 g/m², A5R - Legal, 92.1 × 165.1 (Com6), 114×162 (Youkei2), Max 4 Units Memory upgrade: 1GB/2GB Storage Devices for easy document management: HD-17 SSD hard disk: 64GB HD-18 SSD hard disk: 256GB HD-19 SSD hard disk: 512GB Scan Extension Kit (A): Scan to searchable PDF (embedded OCR) or to MS Office (docx, xlsx, pptx), HD or SD card is needed. CB-5150S: Steel Cabinet (47cm) CB-5150H:Wooden Cabinet (50cm) CB-5150L: Wooden Cabinet (37cm) CB-5150B: Wooden Baseplate (for installation with 4 x PF-5150) Card Reader Holder 12

SECURITY

UG-33: ThinPrint support UG-35: TPM (Trusted Platform Module) USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available **Optional interface:** IB-37: Wireless LAN (802.11a/b/g/n/ac) with Wi-Fi Direct IB-38: Wireless LAN (802.11b/g/n) with Wi-Fi Direct IB-50: Gigabit Ethernet 10BASE-T/100BASE-TX/ 1000BASE-T

IB-51: Wireless LAN Interface (802.11b/g/n) Product Library 14: Installation DVD

WARRANTY

1-year warranty as standard **. KYOCERA quarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYOCERA LIFE

Up to 5-year on-site warranty extensions available for product and options.

WHAT'S IN THE BOX:

Main unit, initial toner, waste toner box, Quick guide, Safety Guide, Operation panel sheet , power supply cord.

¹The device is not designed to achieve the specified volumes in continuous operation.

ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.





KYOCERA Document Solutions Europe B.V. Beechavenue 27, 1119 RA, Schiphol-Rijk Tel +31 (0) 20-654-0000 - Fax +31 (0) 20-653-1256 www.kyoceradocumentsolutions.eu - info@deu.kyocera.com



moorio

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press

All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country



AUG2023ECOSYS PA4500cx/VER1.0